

CHEETAH SCREW INSPECTION MACHINE




WIDE PRODUCT RANGE

Flexible user interface design with custom function libraries makes circular or angular (cornered / hexagonal) formed products can be adjusted easily.

HIGH PRECISION

High-resolution cameras and custom light design lets 50μ - 60μ measurement precision depending on the measurement tools used.



HIGH CAPACITY

Depending on product specifications, capacity can **reach up to 1000 pcs/min.**





RAPID MODEL CHANGE

The easy-to-use feedback interface and the manual mode option allow for fast model change.

CUSTOMIZED FUNCTION LIBRARIES

Flexible software design supports job customization. This feature allows function calls for different measurements or inspections.


Most of the functions can be used for various purposes. Unlimited reference fixture points can be set to define ROIs properly.


Some dimensions that can be inspected are listed below;

Flange diameter, head thickness, head form, thread pitch, thread angle, thread top diameter, shank diameter, dogpoint diameter.

FLEXIBLE PLATFORM

Stations and their features can be changed depending on customer demand and product.





CHEETAH SCREW INSPECTION MACHINE

Product Options	Screws, bolts
Types of Control	Thread form, Dimensional, etc
Operation Range	Ø10 mm x L: 80 mm
Capacity	Up to 1000 pcs/min
Pre Loading	Elevator, linear or bowl vibrator
PLC Group	Beckhoff
Dimension Control	4 high-resolution optical cameras
Precision	50 μ - 60 μ
Power	2 KW
Curent (max)	4,5 Amp
Air Pressure	6 bar
Voltage Range	380 V- 3 Phase - 50 Hz
Machine Dimensions	1530mm x 1690mm x 1940mm
The dimensions that can be controlled for quality	Flange diameter, head thickness, head form, thread pitch, thread angle, thread top diameter, shank diameter, dogpoint diameter



CONTACT US

- Atatürk Organize Sanayi Bölgesi 10010 Sokak No: 21/1 Çiğli 35620 İzmir, Türkiye
- +90 232 325 00 08
- 囪 info@nrmmuhendislik.com.tr
- www.nrmmuhendislik.com.tr
 - nrm-muhendislik

in